

Dewalt Air Compressor D55167 Manual



File Name: Dewalt Air Compressor D55167 Manual.pdf

Size: 2913 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 20 May 2019, 17:52 PM

Rating: 4.6/5 from 826 votes.

Status: AVAILABLE

Last checked: 17 Minutes ago!

In order to read or download Dewalt Air Compressor D55167 Manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dewalt Air Compressor D55167 Manual . To get started finding Dewalt Air Compressor D55167 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dewalt Air Compressor D55167 Manual

You claim must be postmarked on or before October 15, 2016. Download the attached file located at the end of this answer. Photo copies will not be accepted except for RI residents. It is recommended that you make a photo copy of all submitted materials for your records. Note To resolve any potential questions or issues regarding your submission, you may be required to mail or fax these copies. Original UPC barcode cut from the outside product packaging of the DEWALT product purchased. To check the status of your rebate please call 8664445290. Thank you for your interest in DEWALT tools. It has been our pleasure to provide this information. For additional details, disclaimers and exclusions please read the fine print found on the rebate form. Please try again. Please try again. Please try again later. In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Page 1 of 1 Start over Page 1 of 1 In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account New, Bulk Packed. Genuine OEM replacement part. Consult owners manual for proper part number identification and proper installation. Compatible with Black and Decker 91916760, 91916761, 91916762, 91916763 To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify trustworthiness. Please try again later. Amazon Customer 2.0 out of 5 stars The filter I removed from the compressor has a soft rubber casing. It takes some modifications in order for this item to fit my compressor. Had a thicker plastic flange then the rubber flange my previous factory filter had. This makes it so the factory filter cap can't quite clip on. Had to tape the perimeter of the cap to hold in place. <http://atlet-irk.ru/userfiles/boss-bassman-pedal-manual.xml>

- **dewalt air compressor d55167 manual, dewalt air compressor d55167 parts, dewalt air compressor d55168 manual.**

Otherwise it does the trick. Thank you Posted by Davidhokanson 1 month ago Answers Reset Button For Dewalt D55167 Compressor My desalt compressor, d55167, after unplugging and re plugging the compressor. Is there a reset butt. Posted by sowhing 3 years ago Answers View 2 videos for the Dewalt D55167 below. A. Safety Valve H. Regulated Pressure Gauge D. Air Intake Filter Voltage Single Phase 120V Minimum branch circuit requirement 15 A Fuse Type Time delay Replace with a new air tank or replace the entire compressor. See Grounding Instructions under Installation. Compressor will or outlet tubes, can with center or a DeWALT authorized protective shrouds removed service center. Air Compressor Pump The pump compresses air into the air tank. This pressure is open, allowing compressed air to connect operation makes connections simple and easy. When the air compressor reaches cut out setting . Tank Pressure Gauge The tank pressure gauge B indicates the reserve air pressure in the. If these grounding instructions. These impurities may also be met, or if operation of the compressor. CAUTION Certain air compressors can occur to change the cord set. DO NOT USE 14 OR 16 AWG. NOTICE The use an air line filter. WARNING Do not operate this instruction manual for air tools and accessories. DO NOT lift by moisture. Compressed air from the recommended lift points N. Shutdown stairs or steps. When location is functioning properly, see Draining Air Tank under Installation. 3. Ensure safety valve G is reached slowly lower compressor to the OFF. If the safety valve does not work properly, over pressurization may contain substances that are regulated and must be performed by a DeWALT factory service center or a DeWALT authorized service center. Wipe air compressor clean and store in

place.Warning Hot surfaces.EnglishCheck the accessory air requirement. Replace air hose. Operate safety valve manually by your air compressor, a larger compressor is used.<http://www.firewaterdamagedfw.com/test/fckeditor/uploadfiles/boss-bass-chorus-manual.xml>

Contact a DeWALT factory service center or a DeWALT authorized service center. Remove, clean or replace. Replace. If motor overload protection trips frequently, contact a DeWALT factory service center or a DeWALT authorized service center.Possible solution Motor will start automatically when tank pressure drops below cutin pressure of Explosion or Fire warning under Installation. Check fuse box for our particular branch circuit. 2. You should use a fuse or circuit breaker with the filter removed. Refer to the Extension Cords under Important Safety Instructions. 1. Contact a DeWALT.The following terms are frequently used to search for Dewalt D55167 supportGiving Off A Distorted Sound. Can These Be Call the Mastercard Help Center with any. If you have questions or comments, contact us. Pour toute question ou tout commentaire, nous contacter.Pagina 8 WARNING Risk of Unsafe Operation WARNING Risk of FALLING. EnglishPagina 9 SAVE THESE INSTRUCTIONS Tank Pressure GaugeTo ensure Warning. Pagina 11 Extension Cords necessary to operate it from a 20 amp circuit. It is not necessary. If an extension cord must. Pagina 12 Lifting 6. Pull the regulator knob D out and turn counterclockwise until fullyPagina 13 El regulador no cierra la salida de aire 2. Pull the regulator knob D out and turn counterclockwise until fully Maintenance ChartPagina 14 Draining Air Tank Fig. 1 3. Remove filter cover J from base.DeWalt heavy duty industrial tools are warranted for one year from CFM Cubic feet per. Pagina 16 Troubleshooting GuideDo not repair the leak.Pagina 19 Compresseur d'air, modele D55167 FIG. 1 B DPlacer le compresseur d'air sur une surface plane et s'assurer qu'il. Pagina 31 2. Une fois le compresseur a l'endroit voulu, labaisser lentement Avertissement Risque d'utilisation dangereuse. SaisirPagina 33 Verification de la soupape de surete REMARQUE Tous les systemes de compression d'air generentSi la soupape. Pagina 34 Date et lieu de l'achat 2. Permettez a l'unit  de se refroidir.

ReparationsPagina 35 REMPLACEMENT GRATUIT DES ETIQUETTES Code de certifications les produits qui affichent un ou plusieurs. D'AVERTISSEMENT Si les etiquettes d'avertissement deviennent. Pagina 36 Guide de depannageL'operateur ou. Pagina 37 Code Cause probable SOLUTION PROBABLENe pas reparer la fuite. Pagina 38 Code Cause probable SOLUTION PROBABLEPagina 39 Code Cause probable SOLUTION PROBABLEPagina 40 Compresor de aire D55167 FIG. 1Pagina 44 Elementos y accesoriosPagina 45 ADVERTENCIA Riesgo de objetos despedidos ADVERTENCIA RIESGO DE superficies calientesPagina 51 Electricas Preparacion para el uso. Consulte todas las instrucciones de seguridad antes de utilizar laPagina 52 Advertencia Riesgo de explosion. Demasiada presion de Advertencia Riesgo de operacion insegura. Sostenga laPagina 53 NOTE Cualquier tarea de mantenimiento no incluida en esta seccion Advertencia Riesgo de objetos despedidos. Utilice siempreDrene el tanque de aire AccesoriosPagina 55 Para hacer efectiva esta garantia debera presentar su herramienta REEMPLAZO GRATUITO DE LAS ETIQUETAS DEPagina 56 Para reparacion y servicio de sus PARA OTRAS LOCALIDADESPagina 57 Glosario. CFM Pies cubicos por minuto. PSI Libras por pulgada cuadrada; una unidad de medida de presion. SCFM pies cubicos. Pagina 58 Guia de deteccion de problemasPagina 59Codigo causa posible SOLUCION POSIBLENo repare la. Pagina 60Codigo causa posible SOLUCION POSIBLEPagina 61Codigo causa posible SOLUCION POSIBLEPagina 62 Pagina 63 Pagina 64 DeWALT Industrial Tool Co., 701 Joppa Road, Baltimore, MD 21286. For the SPRING, order 514012280. The valve plate assembly is probably the problem. Go to check valve test. These are the "humps" on the back of the motor. Use a capacitor tester or if not available, test continuity across the leads of the capacitor. Try the following This should be held on with 4 long bolts and nuts that run the length of the motor. Use a screwdriver and small hammer to gently remove the end cover.

<https://skazkina.com/ru/4-speed-manual-transmission>

You should also see a round brown disc. Extending from the round disc you should see a long

slender piece of copper or other material, the size of a wooden coffee stirring stick. At the end of this stick are electrical contact points. These points should be "closed". Sometimes corrosion will build up on them. Take an emery file and file between the contact points to clean them. When the motor builds up speed, the small weights on the springs swing out and separate the points. This opens the circuit between the starter capacitor and the motor. One of the round hump capacitors helps to start the motor and when the motor reaches high enough speed the weights and springs open the points and the starter capacitor then stops sending a charge to the motor. At this point, the other capacitor, the run capacitor continues to keep the motor running. If there is corrosion on the points, the starter capacitor never kicks in and helps the motor to start. Do not over tighten belt, it will break the crankshaft or burn up a bearing. Compressors do NOT squeal when the belts slip. It sounds like the motor is slowing down but what is really happening is the belt is slipping. If you have a 230 V motor converted to 120, you may have lost some pulling power. If it is the wrong motor not matching the correct motor pulley you may be overloading the motor. You may have an underpowered motor, or the motor is too small. Look at the amp rating on the motor plate and put an amp probe on the motor if and when it starts bogging down. You could also have under size wire from panel or too long of a run on wire itself from panel. If you dont have an amp probe its recommended to take the motor in to a local repair shop or have an electrician come to your house for further diagnosis. Is oilfree or oilbath best. Will I need a twostage unit or is a singlestage unit sufficient. How much CFM will I require.

<http://www.philipsong.com/images/Cylonix-Shapeshifter-Manual.pdf>

How much PSI will I need Not to say this is unimportant for the homeowner or hobbyist, but there is a compressor for every demand and job out there; the more you know going into it, the easier itll be when youre at the outlet about to make your purchase! Most oilfree units on the market, however, do not put out high CFM, generally 6 CFM or less. Also, these units are generally louder than oilbath units, so if noise is a factor, go with either a "silent" oilfree compressor the "JC10" Rolair unit or any of the California Air Tools units, for instance or an oilbath compressor. Oilbath units are always recommended for longevity, and they simply put out a heck of a lot more CFM than any oilfree unit will be able to manage producing. Most contractors and all industrial applications and commercial garages demand a heavyduty oilbath air compressor as it will put out the CFM you need and will simply last a lot longer than any oilfree unit will. However, if youre a small contractor that has one or two workers, an oilfree unit may be sufficient. If youre simply using a trim gun to install trim in a kitchen, this doesnt demand high CFM so you can probably get away with using a smaller oilfree unit. Your application, whether it be a roofing nail gun, sand blaster or die grinder, will have a CFM requirement specification you can find this in the manual for your tool. You need to choose an air compressor that at least meets that minimum CFM output. If an air compressor doesnt have the required CFM for your tool, it was run constantly and you risk burning the motor, pump or both, and your application will suffer for it as well. Be sure the air compressor puts out the required CFM and ideally a couple more CFM for your application. The CFM spec is related to duty cycle of a unit so well discuss that this term means now.

<https://philippebucaille.com/images/Cylinder-Gauge-Manual.pdf>

Below is a very handy chart and info on what duty cycle means for an air compressor and to give credit where credit is due, this very helpful information comes from VIAIR at Heat dissipation rates may vary depending on ambient temperatures and operating conditions. PSI isnt as important as CFM because most applications dont require high CFM. Any typical air compressor puts out at least 120 PSI, which is sufficient to run any nail gun, grinder or blow gun. It doesnt have anything to do with the number of cylinders or heads the pump has. Also, a twostage unit will recycle quicker pump up quicker and has a higher CFM rating than a singlestage unit. For most homeowners and hobbyists that are using small nail guns, blow guns or pumping up beach balls, a singlestage unit is

definitely sufficient. Even most small contractors can get away with using singlestage units if they have a small crew. And, sometimes buying cheap is worth it if you don't use the air compressor often, so what if the valves crack or piston rings wear out. You can probably buy a replacement for the same amount as a repair would cost. I get it. However, in most cases it is certainly worth it to increase your budget and buy a unit manufactured by a reputable brand you trust; I'm thinking Campbell Hausfeld, Rolair, Jenny, Champion, Ingersoll Rand and Coleman Powermate. Not only will these units typically be of a higher quality, but it's worth it just for the fact that most but not all units made by these manufacturers have replacement parts available, and offer great warranties. They also usually have a large network of authorized service centers available nationwide, so when you need to have the unit repaired, it's convenient to do so. It's the old adage, spend more now so you won't have to down the road. The more you know going into the purchase the better, and knowing what you need will save you money now and later.

The specs and stickers on the unit are not always accurate, and add confusion instead of critical information to buying decisions. Then you can figure the true CFM from the difference in starting and final pressures, times the volume of the tank, divided by the time it took to pump up. You can also time the pumpup cycle from the cutin to the cutout pressure, since that's how one usually runs a compressor. These true performance measurements are impossible to fake. This should be clearly marked on the tank itself by the manufacturer. Record the amount of time that it takes to refill the tank while paying close attention to the compressors tank gauge. You will need to record the psig pounds per square inch at two separate times in the refill process once at the moment the compressor kicks in and once at the moment the compressor kicks out. For example, if the compressor kicks in at 75 psig and kicks out at 100 psig then the difference would be 25 psig. This is the number of cubic feet that your compressor pumps in the time it took for your tank to fill recorded in Step 4. To do this, take the number of cubic feet found in Step 7 and divide it by the number of seconds it took to pump this amount. Multiply the result by 60 and you have the CFM of your air compressor. Why Standard AC cords are limited to 15 amps of current, or about 1800 watts. Then try our Advanced Search section. Click Here or Type the Make, Model or Part Numbers in the search box located in the top, right corner. Follow these steps to keep your compressor running in tiptop shape! Here's how to find out! This instructional document will show you how to polish up the original Crankshaft when installing new Rods so you won't have to! Make sure you break it in to minimize damage to the pump and protect your investment! Does it really matter. We take both air compressors apart to show you what they are made of. How to replace it with a new one. We show you how to replace it with one that is similar in size.

We show you the correct way to install it. Do you order the wrong size and wonder why. Master Tool Repair sells replacement parts for Husky and Workforce products that we obtain. You can unsubscribe at anytime. Subscribe Personal information provided may be collected, used and disclosed in accordance with our Privacy Policy Connect with Us Connect with us on your favourite social networks. We'll let you know what we're up to, and you can tell us how we're doing. Page Count 4 Need to fix your D55146 Type 3 Compressor. Quick Fix How to Replace the Valve Plate on an Air Compressor. Tool Parts Direct. Shop thousands of Dewalt 4.5. Craftsman D27253 Compressor Regulator Dewalt D55146 Compressor OEM Air Regulator. Dewalt Air Compressor D55146 Regulator. File Type Extension pdf. PDF Version 1.4. Linearized No. Author Softplicity. Subject. Page Count 4. Page Mode UseOutlines. Description. Creator Softplicity. Title Dewalt Air Compressor D55146 Regulator. Creator Tool Softplicity. Keywords. Producer Softplicity. Pour toute question ou tout commentaire, nous contacter. Compresseur Compresor de aire sin aceite portatil B. Air Tank Pressure Gauge. C. Regulated Pressure Gauge. D. Regulator. E. Quick Connect G. Safety Valve. H. Air Tank Drain Valve I. Pressure Switch. J. Air Intake Filter. Specifications. Voltage Single Phase 120V. Minimum branch circuit requirement 15 A. Fuse Type Time delay. Specifications Noise Emission Values Sound Pressure Level Emission. Sound Power Level. Uncertainty in the Sound Power

Level. ValuesThe sum of the emission value and the uncertainty is the limitDefinitions. Safety. GuidelinesA DANGER Indicates an imminently hazardous situationCAUTION Indicates a potentially hazardous situation which,NOTICE Indicates a practice not related to personal injuryImportant.

SafetyAlways Operate the CompressorWARNING This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harmIf electrical sparks fromRestrictingTo reduceDo not operate unit indoors orAlways turn off and unplugExposure to chemicalsSprayed materials such asThe compressor is notWork in an area with goodAlways use certified safetyWARNING Risk of BURSTING. Air Tank On February 26, 2002, the U.S. Consumer ProductAir compressor receiver tanks do not have an infinite life. Tank lifeThe exact effect of theseIf proper maintenance procedures are not followed, internal corrosion to the inner wall of the air receiver tank can cause the air tankYour compressor air tank must be removed from service by the endThe following conditions could lead to a weakening of the air tank.The air tank is designedNever use compressor toTiresUse a tire pressure gauge toNOTE Air tanks, compressorsLike any other electrical device, failure to provide adequate grounding could result in serious injurySee Grounding. Instructions under. Installation.Compressor is connectedAlwaysLoose clothes, jewelry, or longBecome familiar with theKeep operating area clear of allKeep children away from the airDo not operate the productStay alert at all times. Never defeat the safety features of this product. Equip area of operation with aCan fall from a table,Never operate compressor on aUse additional air hose to reachObtain assistance fromThis pressure is controlled by theARO. One hand push to connect operation makes connectionsThe drain valve is located at the base of the airAir Tank under. Maintenance.It is normal for this fan to blow air through the vent holes in largeAIR COMPRESSOR PUMP. The pump compresses air into the air tank. Working air is notInstructions. The filter is designedTo ensure A WARNING Risk of Electrical Shock.

In the event of a shortThis air compressor must be properlyThe motor has a thermalTheTo restartMUST be used with a groundedTheDo not use if thereAssemblyCoupler will snap into place.Connect plug on hose.Extension. Cords. It is not necessaryIf an extension cord must be used, be sure it is. CompatibilityInstead of using an extension cord, increase the working reach ofVoltageCircuit. NOTE Always use an air line filter to remove moisture and oil vaporPlace the air compressor in a clean, dry and well ventilated areaKeep the compressor away fromThe ventilation openings on the compressorPlace the air compressor on a flat surface resting on the rubberProtection. Refer to the Voltage and Minimum Branch Circuit Requirements. A CAUTION Certain air compressors can be operated on aElectrical Code. Circuit is not used to supply any other electrical needs. Extension cords comply with specifications. Circuit is equipped with a 15 amp circuit breaker or 15 ampIf any of the above conditions cannot be met, or if operation of theObserve extensionDO NOT liftA WARNING Risk of Unsafe Operation. Ensure proper footing andAlways store compressorNOTE Always use a minimum. A WARNING Risk of unsafe operation. Firmly grasp air hose in handDo not use damaged orToo much air pressure causes aCheck the manufacturer's maximumThe regulator outletChecklistNOTICE Risk of property damage. Compressed air from the unitDo not spray unfiltered air at an item that could be damaged by moisture. Some airRead the instructions for the air tool or device.See Regulator under. Features. WARNING Do not operate this unit until you read this instructionPreStartSee Voltage and Circuit Protection under Installation.Maintenance.Safety Valve under Maintenance. ShutdownA WARNING Risk of unsafe operation. Firmly grasp air hose in handEnsure air tank pressure gauge reads 0 psi. A WARNING Risk of bursting. Drain air tank daily.

Water willMaintenanceThe following procedures must be followed when maintenance orNOTE All compressed air systems contain maintenance parts e.g.,These used partsNOTE Take note of the positions and locations of parts duringNOTE Any service operations not included in this section shouldWhile compressor is pumping to pressure and after pressure cuts out,Chart. Procedure. Daily. Weekly. See tankCheck safety valve. Inspect air filter. Drain air tankChecking. Valve. If the safety

valve does not workA WARNING Risk from flying objects. Always wear certified safetyBefore starting compressor, pull the ring on the safety valve toNOTE Ring mayIf the valve isAir. TankNOTICE Risk of unsafe operation. Do not operate without air inletKeep face and other body parts away fromA WARNING Risk from noise. NOTE All compressed air systems generate condensate thatWARNING Risk of bursting. Drain air tank daily. Water willIf not drained, water will corrode and weakenNOTICE Risk of property damage. Drain water from air tank mayCheckin9. Air. Filter. ElementIf you need assistance in locating any accessory for your tool,Baltimore, MD 21286, call 18004DEWALT 18004339258 or visitUse only accessories ratedModel Number. Serial Number. Date and Place of Purchase. RepairsRisk of burn. Outlet tube, pump head,Allow compressorYear. WarrantyFor warranty repair information,This warranty does notThis warranty gives you specific legalLATIN AMERICA This warranty does not apply to products soldCFM Cubic feet per minute. SCFM Standard cubic feet per minute; a unit of measure of airPSi Pounds per square inch; a unit of measure of pressure. Code Certification. Products that bear one or more of theLaboratories.

CutIn Pressure While the motor is off, air tank pressure dropsWhen the tank pressure drops to a certainThe low pressure atCutOut Pressure When an air compressor is turned on andThe high pressure at which the motor shuts off is called cutoutBranch CircuitThe circuitDuty Cycle This air compressor pump is capable of runningGuide. This section provides a listof the more frequently encountered malfunctions, their causes and corrective actions.The operator or maintenanceProblem. Code. Excessive air tank pressuresafety valve pops off. Air leaks. Air leaks in air tank or at air tank welds.Air leaks from safety valve. Knocking Noise. Pressure reading on the regulated pressure gauge drops when an accessory is used. Compressor is not supplying enough air to operate accessories. Regulator knob has continuous air leak. Regulator will not shut off air outlet. Motor will not run. Squealing Sound.Pressure switch cutout too high. Contact a DEWALT factory service center or a DEWALT authorizedTube fittingS are not tight enOugh. Tighten fitt ngS where air Can be heard escapingl Check f ttingSDo Not Overtighten,Air tank must be replaced. Do not repair the leak. WARNING Risk of bursting. Do not drill into, weld or otherwise modify air tank or it will weaken. The air tank can rupture orLeakingRegulator is not adjuSted correctly for acCesSoryOperate safety valve manually by pulling on ring. If valve still leaks,Features if pressure drop is excessive I. NOTE Adjust the regulated pressure under flow conditions whileProlonged excessive use of air. Decrease amount of air usage.CheckIf it is higheISupp!ied by. Compressor,Replace air hose. Check valve restricted. RemoVe; Clean or replacel. Tighten fittings. Motor overload protection switch has tripped. Refer to Motor Overload Protection under Features. If motor overload protection trips frequently, contact a DEWALT factory serviceMotor wi!! start automatically when tank pressure drops below cutin pressure of pressure switchl.

Extension cord is wrong length or gauge. Check for proper gauge wire and cord length refer to the Extension. Cords under Installation.Contact a DEWALT factory service center or a DEWALT authorizedSafety Instructions.Worn Belt. Contact a DEWALT faot0ry Service Center or a DEWALT authorizedRestricted air intake filter. Clean or replace air intake filter. Do not operate the air compressorRefer to the Air Filter paragraph in the. Maintenance section.Branchements rapides. Clapet. FicheH. Soupape de purge duI. Rembobineur de cordonJ. Filtre dadmission dairTension monophas6, 120V. Exigence minimale du circuit de d6rivation 15 A. Type de fusibletemporisation. FicheValeur de 16missionIncertitude du niveau deNiveau de puissance acoustique. Incertitude du niveau de puissanceLa somme de la valeur de 16mission et de lincertitude 6tablit laA DANGER Indique une situation dangereuse imminente qui, siSe laver les mainsIamiante et le plomb contenus clans les peintures au plomb.Combustible, essence OuLe fonctionnement de ceIobstruction qui pourrait limiterlint6rieur ou dans un endroitToujours 6teindre etFaircomprime sortant duLes mat6riaux vaporis6sTravailler dans un endroitLes r6servoirs dair comprim6 des compresseurs nont pas uneSi les proc6dures ad6quates de maintenance ne sont pas suivies.Les conditions suivantes peuvent amener la d6gradation duVidanger le r6servoir dairAccessoiresPneus. Des pneus

Ne faites jamais effectuer de
Utiliser un manomètre pour
Les
réservoirs
Consulter les directives
Lorsqu'il pleut ou dans des
DEWALT ou un centre local.
CSA Z94.3
munie de crans
Toujours mettre le compresseur
Entretien, de fixer des outils ou
Tenir les cheveux,
Ne pas utiliser l'appareil
Lorsqu'il revient et comprendre toutes les
Se familiariser avec le
Dégager la
zone de travail de
Tenir les enfants hors de portée
Ne pas utiliser le produit en cas
Installer un
extincteur dans la
aide avant de le soulever.

Si le manomètre ne met pas
Selon la durée d'utilisation, le
Lorsque le compresseur d'air atteint la
pression de déclenchement,
Cette pression est contrôlée par
Une fois que la pression désirée est
Il suffit tout simplement d'appuyer
Il faut donner au moteur le temps
de redémarrage
Entretien.
Assemblage
L'air de travail
Saisir les directives
Batteries
Au cas où un
Le
compresseur d'air portatif est muni d'un cordon ayant un fil de
Cette prise BOIT
Si une rallonge doit
être utilisée, s'assurer
Les fils de l'extrémité. Connectez des boyaux supplémentaires au besoin.
Si elle
ne s'insère pas dans
Le circuit n'est pas utilisé pour alimenter d'autres besoins en
Les fusibles de. Si
une des conditions ci-dessus n'est pas satisfaite, ou si le
REMARQUE
Toujours utiliser un filtre de
canalisation d'air pour
Emplacement. Placer le compresseur d'air dans un endroit propre, sec et
bien
Tenir le compresseur
La pompe de compresseur
Placer le compresseur d'air sur une surface plane
et s'assurer qu'il
Consulter toutes les directives de sécurité avant d'utiliser l'appareil. Respecter les
directives de sécurité du cordon d'alimentation le cas
Conduire prudemment pour éviter un
basculement risqué
On doit soulever l'appareil ou le pousser le long d'une rampe.
Consulter la
rubrique Protection de la tension et du circuit sous Installation.
Entretien. AVIS
Risques de
dommages matériels.
Ne pas vaporiser de
Faire non filtré sur un article que
l'humidité
Lire les
directives pour l'utiliser ou le
Consulter la
Poussez le bouton pour le
NOTE
Toujours utiliser
un REVI
ARQUE
Si l'utilisation du compresseur est terminée, suivre
REMARQUE
Toute réparation
non décrite dans cette rubrique. Risque d'utilisation
Purger le réservoir
L'eau se condensera dans le
réservoir d'air. Si
Programme
Procédure
Se reporter à
Vérification de la soupape. Inspecter le filtre à air.
Vidange du réservoir d'air. Recherche de bruits ou de
Vérification des fuites d'air
Nettoyage de la
partie
Mettre le réservoir hors
Alors que le compresseur développe
Risque provenant des objets projet.

<http://www.raumboerse-luzern.ch/mieten/4-speed-manual-transmission>