



File Name: Dewalt Xrp Dc988 Manual.pdf

Size: 1923 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 24 May 2019, 18:31 PM

Rating: 4.6/5 from 818 votes.

Status: AVAILABLE

Last checked: 17 Minutes ago!

In order to read or download Dewalt Xrp Dc988 Manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[❑ Register a free 1 month Trial Account.](#)

[❑ Download as many books as you like \(Personal use\)](#)

[❑ Cancel the membership at any time if not satisfied.](#)

[❑ Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with Dewalt Xrp Dc988 Manual . To get started finding Dewalt Xrp Dc988 Manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

Dewalt Xrp Dc988 Manual

Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. Cordless Drill Dr. If you want to search this text, hold control and F, and type the word you are looking for. Page 1 PALIZA INSTRUCTIVO b Recharge only with the charger specified by the manufacturer. A charger that is suit able for one type of battery pack may create a risk of fire when used with another battery pack. Use of any other SERVICIO po battery packs may create a risk of injury and fire. If contact accidentally occurs, flush with water. If liquid contacts eyes, poadditionally de seek medical help. Liquid ejected from the battery may cause irritation or burns. Taladro replacement parts. This will ensure that the safety of the power tool is maintained. USAR of the tool a live a and shock the operator. Exposure to noise can cause hearing loss. INSTRUCTIVO MC comments Taladro a Use auxiliary handles supplied with the tool. Loss of control can cause personal injury. Temporary hearing loss or serious ear fildrum ww MC Cordless damage may result from high sound levels generated by hammer drilling. DE sans XRP 13mm a Wear safety goggles or other eye protection. Flying particles can cause permanent eye damage. Keep a firm grip on the tool at all times. XRP ALT Do not attempt to operate this tool without holding it with both hands. Wear gloves when touching them. DUTILISATIO DC988 DC988 DC988 Heavy a Avoid prolonged contact with dust from power sanding, sawing, grinding, drilling, para 1 and other construction activities. Wear protective clothing and wash exposed areas perforateurs perforadores with soap and water. Direct particles away from face and body. MANUAL CAUTION When not in use, place tool on its side on a stable surface where it will not Marteaux cause a tripping or falling hazard. <http://arnoldcosterexpeditions.com/userfiles/bovine-embryo-transfer-manual.xml>

- **dewalt xrp dc988 manual, dewalt xrp dc988 manual pdf, dewalt xrp dc988 manual download, dewalt xrp dc988 manual 2017, dewalt xrp dc988 manual instructions.**

DC980 DC984 DC980 DC984 DC980 DC984 CAUTION DO NOT TOUCH ANY METAL PARTS OF THE TOOL when drilling or driving into walls, floors or wherever live electrical wires may be encountered. Hold the tool only by insulated grasping surfaces to prevent electric shock if you drill or drive into a live wire. CAUTION Wear appropriate hearing protection during use. Under some conditions DEWALT Industrial Tool Co., 701 Joppa Road, Baltimore, MD 21286 and duration of use, noise from this product may contribute to hearing loss. EWALT JAN06 Form No. 639282 00 DC980, etc. Read all instructions. The term a power tool a in all Important Safety Instructions for Battery Packs of the warnings listed below refers to your mains operated corded power tool or bat Your tool uses either a 12, 14.4 or 18 Volt DEWALT battery pack. When ordering replacement tery operated cordless power tool. NOTE Your tool will accept either standard or Extended Run Time battery packs. However, be 1 WORK AREA SAFETY sure to select proper voltage. Cluttered or dark areas invite accidents. The battery pack is not fully charged out of the carton. Before using the battery pack and b Do not operate power tools in explosive atmospheres, such as in the presence of charger, read the safety instructions below. Then follow charging procedures outlined. Power tools create sparks which may ignite the dust or fumes. READ ALL INSTRUCTIONS c Keep children and bystanders away while operating a power tool. Distractions can a Do not incinerate the battery pack even if it is severely damaged or is completely worn cause you to lose control. out. The battery pack can explode in a fire. This does not indicate a failure. However, if the outer seal is a Power tool plugs must match the outlet. Never modify the plug in any way. Do not broken and this leakage gets on your skin use any adapter plugs with earthed grounded power tools. Unmodified plugs and a. Wash quickly with soap and water. <http://www.bedrucken24.de/userfiles/bovie-change-a-tip-manual.xml>

If battery liquid gets into your eyes, flush them with clean water for a minimum of 15 minutes and seek immediate medical attention. Medical note The liquid is 25-35% caustic or grounded. Water entering a power tool will cause a Do not carry extra battery packs in aprons, pockets, or tool boxes along with other items increase the risk of electric shock. Never use the cord for carrying, pulling or unplugging the possibly causing severe burns or fire. Damaged EWALT chargers. Replace or repair damaged cords. Make sure your extension cord is in good condition. Never attempt to open the battery pack for any reason. If use. Use of a cord suitable for outdoor use reduces the risk of electric shock. When using battery pack case is cracked or damaged, do not insert into charger. Electric shock or electrocution an extension cord, be sure to use one heavy enough to carry the current your product will require may result. Damaged battery packs should be returned to service center for recycling. draw. An undersized cord will cause a drop in line voltage resulting in loss of power and overheating. The following table shows the correct size to use depending on cord length NOTE Battery storage and carrying caps are provided for use whenever the battery is out of the tool or charger. Remove cap before placing battery in charger or tool. If in doubt, use the next heavier gage. The smaller the gage number, the heavier the cord. WARNING Fire hazard. Do not store or carry battery so that metal objects can contact exposed battery terminals. For example, do not place battery in 3 PERSONAL SAFETY aprons, pockets, tool boxes, product kit boxes, drawers, etc., with loose nails, a Stay alert, watch what you are doing and use common sense when operating a screws, keys, etc. Transporting batteries can possibly power tool.

Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication. A moment of inattention while operating power tools may result in serious personal injury. Hazardous Material Regulations HMR actually prohibit transporting batteries in commerce b Use safety equipment. Always wear eye protection. Safety equipment such as dust or on airplanes i. e., packed in suitcases and carry on luggage UNLESS they are properly masked, non skid safety shoes, hard hat, or hearing protection used for appropriate conditions protected from short circuits. So when transporting individual batteries, make sure that the batteries will reduce personal injuries. Ensure the switch is in the off position before plugging a short circuit. in. Carrying power tools with your finger on the switch or plugging in power tools that have CAUTION Battery pack must be securely attached to tool. If battery pack is detached, the switch on invites accidents. A wrench or The RBRC a Seal a key left attached to a rotating part of the power tool may result in personal injury. The RBRC a Rechargeable Battery Recycling Corporation Seal on the e Do not overreach. Keep proper footing and balance at all times. This enables better control of the power tool in unexpected situations. Do not wear loose clothing or jewellery. Keep your hair, clothing and EWALT. In some areas, it is illegal to place spent nickel cadmium batteries in D gloves away from moving parts. Loose clothes, jewellery or long hair can be caught in the trash or municipal solid waste stream and the RBRC program provides an moving parts. Air vents often cover moving parts and should also be avoided.

<https://labroclub.ru/blog/bosch-hnd-5331-manual-0>

Use of these devices can reduce dust United States to facilitate the collection of spent nickel cadmium batteries. Help protect our related hazards. You may also contact your local recycling center for information on where to drop off the spent battery. Use the correct power tool for your application. The correct power tool will do the job better and safer at the rate for which it was designed. RBRC a is a registered trademark of the Rechargeable Battery Recycling Corporation. Any power tool that Important Safety Instructions for Battery Chargers cannot be controlled with the switch is dangerous and must be repaired. Do not probe with

familiar with the power tool or these instructions to operate the power tool. Power conductive objects. Electric shock or electrocution may result. **WARNING Shock hazard.** Do not allow any liquid to get inside charger. Electric shock may e Maintainpowertools.

Checkformisalignmentorbindingofmovingparts, breakage result.If dam EWALT nickel cadmium **CAUTION Burn hazard.** To reduce the risk of injury, charge only D aged, have the power tool repaired before use. Many accidents are caused by poorly rechargeable batteries. Other types of batteries may burst causing personal injury and damage.**CAUTION** Under certain conditions, with the charger plugged in to the power supply, f Keepcuttingtoolssharpandclean. Properly maintained cutting tools with sharp cutting the exposed charging contacts inside the charger can be shorted by foreign material. Foreign edges are less likely to bind and are easier to control.Always unplug the charger from the power supply when there is no battery pack in the cavity. Unplug charger before tions and in the manner intended for the particular type of power tool, taking into attempting to clean.Use of the power tool for operations different from those intended could result in a hazardous situation.The charger and battery pack are specifically designed to work together.

<http://esdara.com/images/Dacor-Convection-Plus-Manual.pdf>

5 BATTERY TOOL USE AND CARE EWALT recharge a These chargers are not intended for any uses other than charging D a Ensure the switch is in the off position before inserting battery pack. Inserting the able batteries. Any other uses may result in risk of fire, electric shock or electrocution.Page 2 FIG. 1 a Pull by plug rather than cord when disconnecting charger. This will reduce risk of dam B B age to electric plug and cord.Use of improper exten sion cord could result in risk of fire, electric shock, or electrocution.The smaller the gauge number of the wire, the greater the capacity of the cable, that is 16 gauge has more capacity than 18 gauge. When using more than one extension to make up the total length, be sure each individual extension contains at least the minimum wire size. A Recommended Minimum Wire Size for Extension Cords A Total Length of Cord 25 ft. 50 ft. 75 ft. 100 ft. 125 ft. 150 ft. 175 ft. 7.6 m 15.2 m 22.9 m 30.5 m 38.1 m 45.7 m 53.3 m Wire Size AWG 18 18 16 16 14 14 12 a Do not place any object on top of charger or place the charger on a soft surface that might block the ventilation slots and result in excessive internal heat. Place the charg FIG. 2 FIG. 3 er in a position away from any heat source. The charger is ventilated through slots in the top and the bottom of the housing.Take it to an authorized service center.Incorrect reassembly may result in a risk of electric shock, electrocution or fire.This will reduce the risk of electric shock. Removing the battery pack will not reduce this risk.Do not attempt to use it on any other voltage. This does not apply to the vehic D ular charger. **SAVE THESE INSTRUCTIONS FOR FUTURE USE** The center position of the control button locks the tool in the OFF position. Whenchangingthe position of the control button, be sure the trigger is released. Chargers **NOTE** The first time the tool is run after changing the direction of rotation, you may hear a click Your tool uses a 12.0, 14.4,18.

<https://www.formuladesign.com/images/Dacor-Convection-Bake-Oven-Manual.pdf>

0 Volt DEWALT Charger. Your battery can be charged in DEWALT on start up. This is normal and does not indicate a problem. 1 Hour Chargers, 15 Minute Chargers or Vehicular 12 volt charger. Be sure to read all safety Torque Adjustment Collar Fig. 2 instructions before using your charger. Consult the chart on the back cover of this manual for compatibility of chargers and battery packs. Your tool has an adjustable torque screwdriver mechanism for driving and removing a wide array of fastener shapes and sizes and in some models, a hammer mechanism for drilling into Charging Procedure masonry. Circling the collar C are numbers, a drill bit symbol, and in some models, and a ham **DANGER** Electrocutation hazard. 120 volts present at charging terminals. Do not probe with mer symbol. These numbers are used to set the clutch to deliver a torque range. The higher the conductive objects. Danger of electric shock or electrocution.The red charging light will blink continuously indi cating that the charging process has started. Three Speed Gearing Fig. 2 3. The

completion of charge will be indicated by the red light remaining ON continuously. The The three speed feature of your tool allows you to shift gears for greater versatility. To select pack is fully charged and may be used at this time or left in the charger. Slide the gear shifter D all the way to the left. Speed 2 middle torque and speed setting is in the middle position. Speed 3 Using Automatic Tune Up a Mode highest speed setting is to the right. The automatic Tune Up a Mode equalizes or balances the individual cells in the battery pack NOTE Do not change gears when the tool is running. Always allow the drill to come to a complete allowing it to function at peak capacity. Battery packs should be tuned up weekly or after 10 stop before changing gears. To use the Automatic Tune Up a, place the battery pack in the charger and leave it for at least 8 hours. Keyless Single Sleeve Chuck Fig.

3 Your tool features a keyless chuck with one rotating sleeve for one handed operation of the Indicator Light Operation chuck. To insert a drill bit or other accessory, follow these steps. 1. Lock the trigger in the OFF position as previously described. 2. Grasp the black sleeve of the chuck with one hand and use the other hand to secure the tool as shown in Figure 3. Your tool is equipped with an automatic spindle lock mechanism. This allows you to open and close the chuck with one hand. To release the accessory, repeat step 2 above. Charge Indicators WARNING Do not attempt to tighten drill bits or any other accessory by gripping the front Some chargers are designed to detect certain problems that can arise with battery packs. Damage to the chuck and personal injury may result. Problems are indicated by the red light flashing at a fast rate. If this occurs, re insert battery Always lock off trigger switch when changing accessories. If the problem persists, try a different battery pack to determine if the Be sure to tighten chuck with one hand on the chuck sleeve and one hand holding the tool for charger is OK. If the new pack charges correctly, then the original pack is defective and should maximum tightness. If the new battery pack elicits the same trouble indication as the original, have the charger tested at an authorized ser Side Handle vice center. Be sure side handle is hot, it automatically starts a Hot Pack Delay, suspending charging until the battery has cooled. This feature ensures maximum battery life. The red light flashes long, then short while in the Hot NOTE Side handle comes equipped on models DC986, DC987, DC988, Pack Delay mode. DC989. PROBLEM POWER LINE Operation as a Drill Some chargers have a Problem Power Line indicator. When the charger is used with some Turn the collar to the drill bit symbol. Install and tighten the desired drill bit in the chuck. Follow these instructions for best results when drilling. pause.

This indicates the power source is out of limits. The the tool as handle and slide the battery pack firmly into the handle until you hear the lock snap charger will keep the battery pack fresh and fully charged. If the battery pack NOTE To remove the battery pack from the tool, press the release buttons and firmly pull has not been kept on maintenance charge, it may need to be recharged before use. A battery the battery pack out of the tool handle. Turn the collar to the drill bit symbol for drilling or to the hammer symbol for hammerdrilling. AC source. WEAK BATTERY PACKS Chargers can also detect a weak battery. Such batteries are still 3. In such cases, about 10 seconds to the planned operation. For WOOD, use twist bits, spade bits, power auger bits or holesaws. For METAL, use high tion. The charger will then go on to charge the battery to the highest capacity possible. Use a cutting lubricant when drilling metals. The exceptions are cast iron and brass which should be drilled dry. For MASONRY, use carbide Important Charging Notes tipped bits or masonry bits. A smooth, even flow of dust indicates the proper drilling rate. 1. Longest life and best performance can be obtained if the battery pack is charged when the 5. Always apply pressure in a straight line with the bit. DO NOT charge the battery pack in bit biting, but do not push hard enough to stall the motor or deflect the bit. Hold tool firmly to control the twisting action of the drill. RELEASE TRIGGER 2. The charger and battery pack may become warm to touch while charging. This is a normal IMMEDIATELY, remove drill bit from work, and determine cause of stalling. DO NOT condition, and does not indicate a problem. To facilitate the cooling of the battery pack after CLICK TRIGGER OFF AND ON IN AN ATTEMPT TO START A STALLED DRILL a THIS use, avoid placing the charger or

battery pack in a warm environment such as in a metal CAN DAMAGE THE DRILL. This will help prevent 3. If the battery pack does not charge properly jamming. a.

Check current at receptacle by plugging in a lamp or other appliance b. Check to see if receptacle is connected to a light switch which turns power off when you Additional Hammerdrill Operation turn out the lights. 1. When drilling, use just enough force on the hammer to keep it from bouncing excessively c. Drill straight, keeping the bit at a right angle to the work. Do not exert side pressure on the center. When drilling deep holes, if the hammer speed starts to drop off, pull the bit partially out of where easily done previously. DO NOT CONTINUE to use under these conditions. Follow the hole with the tool still running to help clear debris from the hole. You may also charge a partially used pack whenever you desire with Operation as a Screwdriver no adverse affect on the battery pack. Under certain conditions, with the charger plugged into the power supply, the exposed match the speed and torque to the planned operation. Insert the desired fastener accessory into charging contacts inside the charger can be shorted by foreign material. Foreign materials the chuck as you would any drill bit. Set the torque adjustment collar Fig. 2 . Make a few of a conductive nature such as, but not limited to, steel wool, aluminum foil, or any buildup practice runs in scrap or unseen areas to determine the proper position of the clutch collar. Always unplug the charger from the power supply when there is no battery pack in the cavity. Unplug charger before MAINTENANCE attempting to clean. Cleaning 6. Do not freeze or immerse charger in water or any other liquid. CAUTION With the motor running, blow dirt and dust out of all air vents with dry air at least WARNING Shock hazard. Do not allow any liquid to get inside charger. Electric shock may once a week. Wear safety glasses when performing this. Exterior plastic parts may be cleaned result. Although these parts are highly solvent resistant, NEVER CAUTION Never attempt to open the battery pack for any reason.

If the plastic housing of use solvents. CHARGER CLEANING INSTRUCTIONS OPERATION WARNING Shock hazard. Disconnect the charger from the AC outlet before cleaning. Dirt and grease may be removed from the exterior of the charger using a cloth or soft non metallic Variable Speed Switch Fig. 1 brush. Do not use water or any cleaning solutions. To turn the tool on, squeeze the trigger switch A . To turn the tool off, release the trigger switch. Your tool is equipped with a brake. The chuck will stop as soon as the trigger switch is fully Repairs released. To assure product SAFETY and RELIABILITY, repairs, maintenance and adjustment including NOTE Continuous use in variable speed range is not recommended. It may damage the switch brush inspection and replacement should be performed by certified service centers or other and should be avoided. EWALT 1 800 433 9258 or Co., 701 East Joppa Road, Baltimore, MD 21286, call 1 800 4 D visit our website www.dewalt.com. Page 3 5 UTILISATION ET ENTRETIEN DE L'OUTIL ALIMENTA. DEWALT will repair, without charge, any defects due to faulty materials or workmanship for three L'utilisation de tout autre bloc piles risque de causer des blessures ou un incendie. Mettre en court circuit les bornes du bloc accessoires or damage caused where repairs have been made or attempted by others. DEWALT will maintain the tool and replace worn parts caused by normal use, for free, any time 6 SERVICE during the first year after purchase. Une expo LATIN AMERICA This warranty does not apply to products sold in Latin America. En cas de doutes, utiliser le calibre suivant. Le bloc piles pourrait Atré rAt avant tout branchement. Ne pas porter de vAtements amples ni de bijoux. Les outils peuvent Atré dangereux entre les court circuit. Ils agit d'une Corporation. Le chargeur et le bloc piles peuvent devenir chauds au toucher pendant le chargement. Placer le chargeur et le bloc piles A un endroit oA. Ne laisser aucun liquide sinfiltrer dans le d.

Silyatoujours des problèmes de charge, emmener l'outil, le bloc piles et le chargeur A un chargeur. CESSER l'utilisation dans ces conditions. Ne laisser aucun liquide sinfiltrer dans le EWALT. MISE EN GARDE On ne doit en aucun cas tenter d'ouvrir le bloc piles. Autour du collier C se trouvent des chiffres, un symbole de mAcHe et, sur certains modèles, un a NE JAMAIS tenter de raccorder deux chargeurs

lun A lautre. Ne tentez pas de l'alimenter au moyen de toute autre tension. CONSERVER CES CONSIGNES Bouton A trois vitesses daengrenage fig. 2 POUR UTILISATION ULTARIEURE Le bouton A trois vitesses daengrenage permet de changer la vitesse daengrenage, rendant ainsi laoutil encore plus polyvalent. Ne pas les toucher avec des objets conducteurs. Faire tourner le manchon vers la gauche, jusqu'a ce que MC laouverture soit assez grande pour recevoir laaccessoire. Utilisation du mode Tune Up Automatique MC 3. Lorsque le lautilisation du marteau perforateur. DANS LE CHARGEUR en acier A coupe rapide ou des scies cloches. Esto permite 3. Lorsquaon perce des trous profonds et que la vitesse de laoutil commence A ralentir, retirer tener un mayor control de la mAquina herramienta en situaciones inesperadas. No se ponga ropa suelta o joyas. Bien que ces piAces soient trAs b No use la mAquina herramienta si el conmutador no puede encenderla y apagarla. Cualquier mAquina herramienta que no pueda ser controlada con el conmutador es peli grosa y debe ser reparada. Estas medidas courant alternatif avant daen effectuer le nettoyage. Ne pas accidentalement. Esto garantizarA la seguridad de la mAquina GARANTIE DE REMBOURSEMENT DE 90 JOURS herramienta. El con gral, sans aucun problAme. tacto con un cable con corriente harA. La placement gratuite. Sujete fermemente la herramienta en todo momento. No intente hacer funcionar esta herramienta sin sujetarla con sus dos manos. A ADVERTENCIA ! Lea todas las instrucciones. ADVERTENCIA Toda persona que entre al Area de trabajo deberA.

Los accidentes abundan en las tenga dificultad para respirar. Puede encontrar la mAscara antipolvo apropiada aprobada por Areas de trabajo desordenadas u oscuras. Algunas her que pueden inflamar el polvo o los gases. Las distracciones pueden hacerle perder el control. Tan solo tome la herramienta por sus partes aisladoras con el fin de prevenir un 2 SEGURIDAD ELACTRICA electrochoque en caso de taladrar o atornillar un cable activado. Bajo ciertas riente. JamAs modifique el enchufe de ninguna manera. Los enchufes no modificados dida auditiva. En caso de duda, utilice el de NOTA Su herramienta aceptarA. A continuaciAn, siga los procedimientos de carga indicados. Esto no indica la existencia de un defecto. ADVERTENCIA Peligro de incendio. El cargador mantendrA. Si no se ha dejado la debidamente protegidas de hacer cortocircuito. En tales casos, herramienta. A continuaciAn el cargador procederA. RBRC es una marca registrada de Rechargeable Battery Recycling Corporation. b. Verifique si la toma estA. Importantes instrucciones de seguridad para c. NO CONTINAE usAndola en estas circunstancias. PELIGRO Peligro de electrocuciAn. Hay 120 voltios en las terminales de carga. No haga Siga los procedimientos de carga. Bajo ciertas condiciones, cuando el cargador estA. Para reducir el riesgo de lesiones, cargue tan solo material externo. Los materiales externos de naturaleza conductora, como el alambre de EWALT. Desconecte siempre el cargador de la toma de corriente PRECAUCIAN Bajo ciertas condiciones, cuando el cargador estA. Desconecte siempre el cargador de la toma de corriente, los contactos de carga expuestos dentro del cargador pueden hacer cortocircuito corriente antes de limpiarlo. Desconecte siempre el cargador de la toma de corriente en el cargador. Para apagarla, suelte el electrocuciAn. interruptor. Su herramienta estA. El portabrocas se detendrA. Cuando use mAs de una extensiAn para lograr interruptor, lo cual hay que evitar.

Coloque el cargador en un lugar alejado de cualquier fuente de calor. Para seleccionar un nAmero, girar hasta que el nAmero deseado electrocuciAn o incendios. quede alineado con la flecha. El dispositivo de tres velocidades de la herramienta le permite cambiar los engranajes para a NUNCA intente conectar 2 cargadores juntos. Deslice el cambiador de engranaje D hasta alcanzar estAndar 120 volts . No intente usarlo con ningAn otro voltaje. Esto no es aplicable al la completa izquierda. La velocidad 2 torsiAn y velocidad mediana estA. GUARDE ESTAS INSTRUCCIONES NOTA No haga cambio de engranajes cuando la herramienta estA. De tener PARA SU FUTURA UTILIZACIAN problemas en cambiar los engranajes, verificar que el cambiador de engranajes estA. AsegArese de leer todas las instrucciones de seguridad antes de usar su car La herramienta dispone de un portabrocas sin llave con un manguito rotatorio para operar el gador. Consulte el cuadro en la parte posterior de este manual para ver la compatibilidad de portabrocas con una sola mano. Para insertar

una broca u otro accesorio, siga estos pasos cargadores y unidades de alimentaciAn 1.
CierreelinterruptordedisparoinmovilizAndoloenlaposiciAn APAGADO como se describe.
Procedimiento de carga 2.

Asirelmanguitonegrodelportabrocaconunamanoyusarlaotraparasujetarlaherramienta PELIGRO
Peligro de electrocuciAn. Hay 120 volts en las terminales de carga. No haga como se demuestra en
la Figura 3. Girar el manguito en sentido antihorario lo suficiente para pruebas con objetos
conductores. La luz roja carga parpadearA.ADVERTENCIA No trate de apretar las brocas u otro
accesorio agarrando la parte frontal del portabrocas y encendiendo la herramienta. Para usar el
Tune Up lo menos durante 8 horas. Page 7 TORREON, COAH Mango lateral Blvd. Independencia, 96
Pte. Col. Centro 871 716 5265 PRECAUCIAN Sostenga siempre el taladro con ambas manos y use el
VERACRUZ, VER mango lateral si la herramienta viene equipada con uno.

IDENTIFICACIAN DEL PRODUCTO Sello o firma del Distribuidor. Instale y apriete la broca deseada
en el portabroca.Son excepciones el hierro fundido y el bronce, a Cuando el producto se hubiese
utilizado en condiciones distintas a las normales; los que se deben taladrar en
seco.ApliquesiemprealtaladrounapresiAnalineadaconlabroca. EjercasuficientepresiAnpara todas al
final de este certificado.Sujete firmemente el taladro para controlar la fuerza de torsiAn de la broca.
adquirir partes, refacciones y accesorios originales. 7. SI EL TALADRO SE ATASCA, esto puede
deberse probablemente a que se encuentra sobrecargado. Al taladrar, use apenas la fuerza
suficiente como para evitar que salte excesivamente o la tener otros dependiendo del estado o la
provincia en que se encuentre.Taladrar en forma recta, manteniendo la broca en Angulo recto con la
pieza. No ejerza EWALT mantendrA.Regule el collar de ajuste de torsiAn Fig. 2 . Haga algunos
ensayos en responder a ninguna pregunta.Use gafas de seguridad cuando ejecuta esto.Desconectar
el cargador del tomacorriente de corriente alterna antes de limpiar. Se puede quitar el sucio y la
grasa de la superficie exterior del cargador con un trapo o un cepillo suave no metAlico. No usar
agua o soluciones de limpieza. Accesorios Los accesorios que se recomiendan usar con su
herramienta estAn disponibles a un costo adicional en su centro de servicio local. PRECAUCIAN
Puede ser peligroso usar cualquier accesorio no recomendado. Estas organizaciones prestan servicio
a las herramientas ESPECIFICATIANS EWALT y emplean siempre refacciones legítimas DEWALT.
Americana Sector Juarez 33 3825 6978 COL.Centro 222 246 3714 QUERETARO, QRO Av. Madero
139 Pte. Col. Centro 442 214 1660 SAN LUIS POTOSI, SLP Av. Universidad 1525 Col. X indique que
le bloc piles naest pas compatible avec ce chargeur. All charge times are approximate. Actual charge
time may vary. Read the instruction manual for more specific information.

<http://www.diamondsinthemaking.com/content/bosch-hnd-5331-manual>